

ETFE RTD WIRE BRAIDED SHIELD

PRODUCT DESCRIPTION

Conductor	Stranded
AWG Sizes	#16 AWG - #26 AWG
Insulation / Jacket Type	(ETFE) 150C
Color Code	2C (Red / White) / 3C (Red/Red/White) 4C (Red/Red/White/White)
Conductor Material	Silver Plated Copper
Shield Type	Braided Shield / Twisted
Approvals	Rohs / Reach Compliant
Applications	Resistance Temperature Detectors / Thermometers / Sensors
Physical Properties	Excellent resistance to abrasion, gasoline, oil, moisture and acid

Part#	Conductor	Insulation Thickness	Overall Diameter *	Weight lbs/k ft	Temp Rating	Voltage
R1692BZ	2c - 16/19	.006"	.183"	33.7	150C	n/a
R1693BZ	3c - 16/19	.006"	.193"	43.4	150C	n/a
R1694BZ	4c - 16/19	.006"	.216"	59.7	150C	n/a
R1892BZ	2c - 18/19	.006"	.171"	28.5	150C	n/a
R1893BZ	3c - 18/19	.006"	.180"	36.1	150C	n/a
R1894BZ	4c - 18/19	.006"	.195"	44.5	150C	n/a
R2072BZ	2c - 20/7	.006"	.153"	21.7	150C	n/a
R2073BZ	3c - 20/7	.006"	.161"	26.9	150C	n/a
R2074BZ	4c - 20/7	.006"	.174"	32.7	150C	n/a
R2272BZ	2c - 22/7	.006"	.137"	16.7	150C	n/a
R2273BZ	3c - 22/7	.006"	.143"	20.2	150C	n/a
R2274BZ	4c - 22/7	.006"	.154"	24.2	150C	n/a
R2472BZ	2c - 24/7	.006"	.125"	13.5	150C	n/a
R2473BZ	3c - 24/7	.006"	.130"	16.0	150C	n/a
R2474BZ	4c - 24/7	.006"	.140"	18.8	150C	n/a
R2672BZ	2c - 26/7	.006"	.115"	11.2	150C	n/a
R2673BZ	3c - 26/7	.006"	.120"	12.9	150C	n/a
R2674BZ	4c - 26/7	.006"	.128"	14.9	150C	n/a