

ETFE RTD WIRE FOIL SHIELDED

PRODUCT DESCRIPTION

Conductor	Stranded
AWG Sizes	#16 AWG - #26 AWG
Insulation / Jacket Type	(ETFE) 150C
Color Code	2C (Red / White) / 3C (Red/Red/White) 4C (Red/Red/White/White)
Conductor Material	Silver Plated Copper
Shield Type	Shielded / Twisted
Approvals	Rohs / Reach Compliant
Applications	Resistance Temperature Detectors / Thermometers / Sensors
Physical Properties	Excellent resistance to abrasion, gasoline, oil, moisture and acid

Part#	Conductor	Insulation Thickness	Overall Diameter *	Weight lbs/k ft	Temp Rating	Voltage
R1692SZ	2c - 16/19	.006"	.154"	27.5	150C	n/a
R1693SZ	3c - 16/19	.006"	.164"	36.4	150C	n/a
R1694SZ	4c - 16/19	.006"	.181"	45.4	150C	n/a
R1892SZ	2c - 18/19	.006"	.142"	21.2	150C	n/a
R1893SZ	3c - 18/19	.006"	.151"	28.1	150C	n/a
R1894SZ	4c - 18/19	.006"	.166"	35.2	150C	n/a
R2072SZ	2c - 20/7	.006"	.124"	14.8	150C	n/a
R2073SZ	3c - 20/7	.006"	.132"	19.4	150C	n/a
R2074SZ	4c -20/7	.006"	.145"	24.2	150C	n/a
R2272SZ	2c -22/7	.006"	.108"	10.3	150C	n/a
R2273SZ	3c - 22/7	.006"	.114"	13.3	150C	n/a
R2274SZ	4c - 22/7	.006"	.125"	16.4	150C	n/a
R2472SZ	2c - 24/7	.006"	.096"	8.2	150C	n/a
R2473SZ	3c - 24/7	.006"	.101"	10.2	150C	n/a
R2474SZ	4c -24/7	.006"	.111"	12.3	150C	n/a
R2672SZ	2c - 26/7	.006"	.086"	6.1	150C	n/a
R2673SZ	3c - 26/7	.006"	.091"	7.4	150C	n/a
R2674SZ	4c - 26/7	.006"	.099"	8.8	150C	n/a