

FEP RTD WIRE BRAIDED SHIELD

PRODUCT DESCRIPTION

Conductor	Stranded
AWG Sizes	#16 AWG - #26 AWG
Insulation / Jacket Type	Fluorinated Ethylene Propylene (FEP) 200C
Color Code	2C (Red / White) / 3C (Red/Red/White) 4C (Red/Red/White/White)
Conductor Material	Silver Plated Copper
Shield Type	Braided Shield / Twisted
Approvals	Rohs / Reach Compliant
Applications	Resistance Temperature Detectors / Thermometers / Sensors
Physical Properties	Excellent resistance to abrasion, oil, moisture , acid and low smoke

Part#	# Conductor AWG	Insulation Thickness	Overall Diameter *	Weight	Temp Rating	Voltage
R1692B	2c - 16/19	.006"	.183"	35.5	200C	n/a
R1693B	3c - 16/19	.006"	.193"	45.6	200C	n/a
R1694B	4c - 16/19	.006"	.216"	62.3	200C	n/a
R1892B	2c - 18/19	.006"	.171"	30.2	200C	n/a
R1893B	3c - 18/19	.006"	.180"	38.1	200C	n/a
R1894B	4c - 18/19	.006"	.195"	46.8	200C	n/a
R2072B	2c - 20/7	.006"	.153"	23.1	200C	n/a
R2073B	3c - 20/7	.006"	.161"	28.5	200C	n/a
R2074B	4c -20/7	.006"	.174"	34.6	200C	n/a
R2272B	2c -22/7	.006"	.137"	17.9	200C	n/a
R2273B	3c - 22/7	.006"	.143"	21.6	200C	n/a
R2274B	4c - 22/7	.006"	.154"	25.8	200C	n/a
R2472B	2c - 24/7	.006"	.125"	14.6	200C	n/a
R2473B	3c - 24/7	.006"	.130"	17.2	200C	n/a
R2474B	4c -24/7	.006"	.140"	20.3	200C	n/a
R2672B	2c - 26/7	.006"	.115"	12.1	200C	n/a
R2673B	3c - 26/7	.006"	.120"	14.0	200C	n/a
R2674B	4c - 26/7	.006"	.128"	16.2	200C	n/a