

PFA RTD WIRE SHIELDED

PRODUCT DESCRIPTION

Conductor	Stranded
AWG Sizes	#16 AWG - #26 AWG
Insulation / Jacket Type	(PFA) 260C
Color Code	2C (Red / White) / 3C (Red/Red/White) 4C (Red/Red/White/White)
Conductor Material	Nickel Plated Copper
Shield Type	Foil Shielded / Twisted
Approvals	Rohs / Reach Compliant
Applications	Resistance Temperature Detectors / Thermometers / Sensors
Physical Properties	Excellent resistance to abrasion, oil, moisture , acid and low smoke

Part#	# Conductor AWG	Insulation Thickness	Overall Diameter *	Weight lbs/k ft	Temp Rating	Voltage
R1692S2P	2c - 16/19	.006"	.154"	28.8	260C	n/a
R1693S2P	3c - 16/19	.006"	.164"	37.9	260C	n/a
R1694S2P	4c - 16/19	.006"	.181"	47.3	260C	n/a
R1892S2P	2c - 18/19	.006"	.142"	22.4	260C	n/a
R1893S2P	3c - 18/19	.006"	.151"	29.5	260C	n/a
R1894S2P	4c - 18/19	.006"	.166"	36.9	260C	n/a
R2072S2P	2c - 20/7	.006"	.124"	15.7	260C	n/a
R2073S2P	3c - 20/7	.006"	.132"	20.5	260C	n/a
R2074S2P	4c -20/7	.006"	.145"	25.5	260C	n/a
R2272S2P	2c -22/7	.006"	.108"	11.1	260C	n/a
R2273S2P	3c - 22/7	.006"	.114"	14.2	260C	n/a
R2274S2P	4c - 22/7	.006"	.125"	17.5	260C	n/a
R2472S2P	2c - 24/7	.006"	.096"	8.8	260C	n/a
R2473S2P	3c - 24/7	.006"	.101"	11.0	260C	n/a
R2474S2P	4c -24/7	.006"	.111"	13.2	260C	n/a
R2672S2P	2c - 26/7	.006"	.086"	6.6	260C	n/a
R2673S2P	3c - 26/7	.006"	.091"	8.1	260C	n/a
R2674S2P	4c - 26/7	.006"	.099"	9.6	260C	n/a