

Aerospace Part#: 8802npfa

(UL) TYPE PFAH

DESCRIPTION

1 Conductor AWG 2/665x30 NPC
UL PFAH Wire 250C 600V

PHYSICAL PROPERTIES

Conductors

Insulation

# Conductors	AWG	Material	Material	Wall	Finished OD
1	2/665x30	Nickel Plated Copper	PFA	.030"	.395"

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
UL Rated -80C to 250C	234.5 lbs / m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage
UL Rated 600 Volts

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

NEC / (UL) Specification	UL TYPE PFAH
Reach / RoHS Compliant	YES
Suitability	Indoor, Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid
Flame Test	VW-1 / UL 1581 / IEEE 383

MISCELLANEOUS

Markings: E161093 2 AWG (PFA) 600V (UL) TYPE PFAH 250C

Color: TBD

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

* Specification subject to error and may change without notice